

Military Grade Double Doors One End Standard 20' X 8' 6" Dry Freight ISO Cargo Container

STANDARD FEATURES

- Ammunition Grade Side-Opening Container
- · Corrugated steel sides, roof, and swing doors on (1) end
- Two-way laden forklift pockets
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- Wall tie down steel lashing rings, 4,000 lbs. cap. each (24 total) tested at 6,000 lbs.
- Front corner post tie downs (10 total)
- Door corner post tie downs (10 total) = restraint system, shoring slot will support 2" x 6" lumber
- · Vents, (2) each


OPTIONAL FEATURES

- · Manifest box (2) each
- · 2nd set unladen forklift pockets
- 383 Green exterior CARC paint

Discount for purchases above 15 Cost does not include shipping Manufactured in the USA

Cost per unit: \$28,620.00 USD





ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

SB861.6	LENGTH (+0/-6)		HEIGHT (+0/-5)		WIDTH (+0/-5)		DOOR OPENING (+0/-5)	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft. in.	19' 10 1/2"	19' 4 13/64"	8' 6"	7' 10 3/8"	8' 0"	7' 8 19/32"	7' 6 1/32"	7' 8 1/8"
Metric	6,058	5,898	2,591	2,397	2,438	2,352	2,287	2,340
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs.	4,780		48,130		52,910		1,176 Cu. Ft.	
Kgs.	2,170		21,830		24,000		33.3 Cu. M.	

ISO 9001



CONTRACT # GS-02F-0024P

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS